

The Art of Music Reproduction



3510 Mono Amplifier

Outputs

Power Output :	100W per channel, 8 Ohms
Frequency Response :	-3dB at 60kHz, ref 1kHz
Total Harmonic Distortion :	<0.01% @ 1kHz, ref rated power
Signal to Noise Ratio :	>110dB, A weighted, ref rated output

Inputs

Input Impedance :	50K Ohms at 1kHz, unbalanced input
Input Sensitivity	
(Unbalanced Input) :	1.75V @ 1kHz
(Balanced Input) :	875mV each input @ 1kHz

General

Mains Supply :	110/120V or 220/240V, 50/60Hz (factory set)
Fuse :	T8AL for 110/120V units T4AL for 220/240V units
Power Consumption :	<400W, 8 Ohms load
Dimensions (HxWxD) :	115mm x 440mm x 300mm
Net Weight :	12kg
Gross Weight :	14kg

Features

- Large custom made toroidal transformer and smoothing capacitors for power supply
- All bipolar transistor design using carefully selected parts
- DC coupled throughout
- Electronic, non-invasive overload protection circuit and thermal trip
- Balanced & Unbalanced Input
- Bi-wire speaker outputs using high quality shrouded sockets
- High quality all aluminium case work
- Three year guarantee
- Available in black or titanium

